OFFICIAL ENTRY BLANK



MAYHEM AT THE MILE 2018 - JUNE 9TH, 2018

COMPLETE ENTRY BLANK BELOW. MAIL TO THE ADDRESS AT THE BOTTOM OF THIS PAGE BY JUNE 1ST, 2018.

CAR NO. DESIRED (CAN BE A 1, 2, OR 3 DI		ME					
(PLEASE CHECK) FU	ULL SIZE CAR	FWD COMPACT CA	AR	POWDERPUFF (WOMEN ONLY / \$50 ENTRY) ANY PARTICIPATING COMPACT CAN COMPETE IN POWDERPUFF; MUST PAY ADDITIONAL\$50 ENTRY FEE. POWDERPUFF FOLLOWS COMPACT RULES.			
ADDRESS			CITY				
STATE	ZIPC	ODE	PHONE NO				
DRIVER'S LICENSE NO.							
DESCRIPTION OF CAR							
EMAIL ADDRESS							

THE DRIVER AND CAR WILL BE PERMITTED WITH A SINGLE REGISTRATION FEE OF \$50.00. ADDITIONAL CREW MEMBERS WILL BE PERMITTED AT \$10.00 PER CREWMAN.

W-9 (ATTACHED) MUST BE COMPLETED AND SUBMITTED WITH THIS FORM IN ORDER TO RECEIVE PURSE MONEY

SEND REGISTRATION FORM, ALONG WITH REGISTRATION FEE, TO:

MOTOR MILE SPEEDWAY - 6749 LEE HIGHWAY - RADFORD, VA - 24141

NO REFUNDS, NO EXCEPTIONS. THERE WILL BE A \$30.00 CHARGE FOR BAD CHECKS; CHECKS IN QUESTION WILL BE TURNED OVER TO LAW ENFORCEMENT.



Form (Rev. August 2013) Department of the Treasury

Request for Taxpayer Identification Number and Certification

Give Form to the requester. Do not send to the IRS.

IIICOIII	all hoveride dervice						
	Name (as shown on your income tax return)						
ge 2.	Business name/disregarded entity name, if different from above						
on pa	Check appropriate box for federal tax classification: Individual/sole proprietor C Corporation S Corporation Partnership Trust/		Exemptions (see instructions):				
pe			Exempt payee code (if any)				
Print or type See Specific Instructions on page	☐ Limited liability company. Enter the tax classification (C=C corporation, S=S corporation, P=partnership) ▶		Exemption from FATCA reporting code (if any)				
돌등	☐ Other (see instructions) ►		¥ .				
pecific	Address (number, street, and apt. or suite no.)	ester's name and	me and address (optional)				
See S	City, state, and ZIP code						
	List account number(s) here (optional)						
Pa	Taxpayer Identification Number (TIN)						
	r your TIN in the appropriate box. The TIN provided must match the name given on the "Name" line	Social securi	ty number				
to avoid backup withholding. For individuals, this is your social security number (SSN). However, for a resident alien, sole proprietor, or disregarded entity, see the Part I instructions on page 3. For other entities, it is your employer identification number (EIN). If you do not have a number, see <i>How to get a</i>							
	TIN on page 3.						
	a. If the account is in more than one name, see the chart on page 4 for guidelines on whose ber to enter.	Employer ide	er identification number				
Hum							
	rt II Certification		7/ 7/ 7/				
Unde	er penalties of perjury, I certify that:						
1. TI	he number shown on this form is my correct taxpayer identification number (or I am waiting for a num	ber to be issue	ed to me), and				
S	 I am not subject to backup withholding because: (a) I am exempt from backup withholding, or (b) I have not been notified by the Internal Revenue Service (IRS) that I am subject to backup withholding as a result of a failure to report all interest or dividends, or (c) the IRS has notified me that I an no longer subject to backup withholding, and 						
3. 1 a	I am a U.S. citizen or other U.S. person (defined below), and						
4. Th	ne FATCA code(s) entered on this form (if any) indicating that I am exempt from FATCA reporting is co	orrect.					
beca intere gene	iffication instructions. You must cross out item 2 above if you have been notified by the IRS that you ause you have failed to report all interest and dividends on your tax return. For real estate transactions est paid, acquisition or abandonment of secured property, cancellation of debt, contributions to an in erally, payments other than interest and dividends, you are not required to sign the certification, but you uctions on page 3.	s, item 2 does r dividual retiren	not apply. For mor nent arrangement	tgage (IRA), and			
Sign	n Signature of						

General Instructions

Signature of U.S. person ▶

Section references are to the Internal Revenue Code unless otherwise noted.

Future developments. The IRS has created a page on IRS.gov for information about Form W-9, at www.irs.gov/w9. Information about any future developments affecting Form W-9 (such as legislation enacted after we release it) will be posted on that page

Purpose of Form

Here

A person who is required to file an information return with the IRS must obtain your correct taxpayer identification number (TIN) to report, for example, income paid to you, payments made to you in settlement of payment card and third party network transactions, real estate transactions, mortgage interest you paid, acquisition or abandonment of secured property, cancellation of debt, or contributions you made to an IRA.

Use Form W-9 only if you are a U.S. person (including a resident alien), to provide your correct TIN to the person requesting it (the requester) and, when applicable, to:

- Certify that the TIN you are giving is correct (or you are waiting for a number to be issued).
- 2. Certify that you are not subject to backup withholding, or
- 3. Claim exemption from backup withholding if you are a U.S. exempt payee. If applicable, you are also certifying that as a U.S. person, your allocable share of any partnership income from a U.S. trade or business is not subject to the

withholding tax on foreign partners' share of effectively connected income, and

4. Certify that FATCA code(s) entered on this form (if any) indicating that you are exempt from the FATCA reporting, is correct.

Note. If you are a U.S. person and a requester gives you a form other than Form W-9 to request your TIN, you must use the requester's form if it is substantially similar to this Form W-9.

Definition of a U.S. person. For federal tax purposes, you are considered a U.S. person if you are:

- An individual who is a U.S. citizen or U.S. resident alien,
- A partnership, corporation, company, or association created or organized in the United States or under the laws of the United States,
- · An estate (other than a foreign estate), or

Date >

• A domestic trust (as defined in Regulations section 301.7701-7).

Special rules for partnerships. Partnerships that conduct a trade or business in the United States are generally required to pay a withholding tax under section 1446 on any foreign partners' share of effectively connected taxable income from such business. Further, in certain cases where a Form W-9 has not been received, the rules under section 1446 require a partnership to presume that a partner is a foreign person, and pay the section 1446 withholding tax. Therefore, if you are a U.S. person that is a partner in a partnership conducting a trade or business in the United States, provide Form W-9 to the partnership to establish your U.S. status and avoid section 1446 withholding on your share of partnership income.



RULES AND REGULATIONS: FULL SIZE CARS

This Demolition Derby is promoted as an unusual spectator attraction. In the interest of safety, Drivers and Mechanics are subject to and must obey the following rules and regulations which are set up by the promoter and the track where this event is being held.

- 1-Each driver must fill out an entry blank and pay a \$50.00 entry fee. Entry fee includes driver and car. Any other crew members will have to pay a \$10.00 pit fee. All drivers must supply their own cars. Only one entry per person per class. Proof of ownership may be required on each car entered.
- 2-Must be at least 16 years of age to drive. Drivers under 18 years of age must have notarized release form signed by his or her parents or guardian.
- 3-Officials reserve the right to approve or reject any entry.
- 4-Consumption of alcoholic beverages in pit area is strictly prohibited. Any driver or pit person under the influence of drugs or alcohol will be immediately disqualified and removed from the grounds. Driver and crew will be subject to sobriety testing.
- 5-Any driver or crew member disobeying the rules will cause his or her car to be disqualified.
- 6-Unsportmanlike conduct will not be tolerated and will be grounds for disqualification and barring from future derbies. Drivers are responsible for the actions of their crew members.
- 7-Drivers and crews are responsible for any damages caused by their negligence on the track or in the pit area.
- 8-All drivers and crews are responsible for picking up trash, automobile parts, scrap metal, tires, etc. from their car.
- 9-All cars must be hauled away the night of the show. Cars left overnight will become property of Shelor Motor Mile, unless a later date of pickup is cleared with officials before you leave the night of the show.
- 10-Reckless driving in the pit area will result in disqualification.
- 11-ALL CARS MUST REGISTER AT LEAST 2 HOURS PRIOR TO START TIME.

Purses

Full Size	Compact
1 st - \$3,500	1 st - \$3,500
2 nd - \$1,000	2 nd - \$1,000
3 rd - \$500	3 rd - \$500

- -Each heat will pay \$50 to the winner.
- -Powderpuff contest will be winner-take-all, and will pay 100% of entries.

Towing and Transportation of Cars

Towing and transportation of derby cars to and from the event location must meet highway safety codes (Including proper light controls, Safety chains, Tow bars, Trailers and rollbacks)

Type of Car

Any Two-Wheel Drive Hard Top or Station Wagon is allowed. NO CONVERTIBLES OR JEEPS ALLOWED.

PREPARATION OF CAR

Trim and Glass

- 1-All glass, chrome, plastic and molding must be removed from the car.
- 2-All wheel weights must be removed.
- 3-Auto must be swept clean. No Junk tires, Wheels, Metal parts, Broken glass, etc. allowed in the car.

Gas Tank

- 1-All tanks must be removed from under the car.
- 2-Gas tank must be a steel tank; NO PLASTIC TANKS.
- 3-Gas Tanks must be in back seat area, securely fastened to the body of the car, and covered.
- 4-Gas Tank Protectors are allowed. They cannot support or be tied into the frame of the car or support the door of the car in any way.
- 5-If a car is leaking gas in any way it will be disqualified from the event.

Rear Suspensions

1-Leaf springs are allowed.

- 2- You can weld spacer blocks to set height of the car (Spacers cannot reinforce the frame in any way.)
- 3- No More Than 7 leafs and no wider than 3 inches.
- 4-No more than 6 clamps per side.
- 5-Rear bumper height no lower than 18 inches from bottom of bumper.
- 6-Aftermarket suspension parts are permitted, Part must not add additional bracing from

factory part.

Front Suspension

- 1-Front suspension may be locked or welded.
- 2-A arms only may be welded directly to the frame (No adding of metal or reinforcing of the frame.)
- 3-Front bumper height no more than 24 inches from bottom of bumper.
- 4-Leaf springs may be run, No more than 7 leafs and no wider than 3 inches.
- 5-If leaf springs are run in the front you have to run a straight axle.
- 6-No more than 6 clamps per side.
- 7-Aftermarket suspension parts are permitted, Part must not add additional bracing from factory part.
- 8-Reinforced or aftermarket tie rod ends and draglink permitted.
- 9-Any passenger car steering box is allowed. If you use a different steering box other than factory it must be mounted to the frame. You may make a bracket for the steering box to mount to the frame. You may weld the bracket to the frame. No adding metal, gussets, or bracing other than the single bracket to the frame.

Doors

- 1-All doors may be welded solid with flat bar no larger than $\frac{1}{2}$ " thick x 3 inches wide.
- 2-Door may be wired or chained.

Trunk

- 1-Trunk seams may be welded solid with a strap no larger than ¼" thick x 3 inches wide.
- 2-Trunk may be pre bent or tucked.
- 3-You can run a bar from the roof to no further than half of the trunk lid.

Cage

- 1-A cage is mandatory. It must consist of a driver's door bar and a passenger door bar, bars no smaller than 4 inch wide and no larger than 12 inches wide. You must run a front and rear bar from door bar to door bar. It must be no smaller than 2 inches and no larger than 6 inches. If you have down bars off of your cage they must be welded to sheet metal only. You may tie the driver's side door bar to the frame (Driver's side only). It must be straight off of the door bar to the frame.
- 2-Gas tank protectors may be run, no larger than 4 inch bar run from end of door bar to end of door bar and a 4 inch bar run on both sides of the gas tank.

- 3-Rollover bars are permitted. Can be welded to cage. Cannot be welded to the frame.
- 4-(2) Kickers are allowed no larger than 2 inches. They must run from front dash bar to frame rail just behind the A arms. IF THE KICKERS ARE LARGER THAN 2 INCHES YOU WILL BE REQUIRED TO REMOVE THE KICKERS. NO EXCEPTION TO THIS RULE. If you are running a Chrysler Imperial or Ford Crown Victoria Police Car or Emergency Service Vehicle with a P71 frame you cannot run any kickers.

Hood and Core Support

- 1-Core support may be bolted with all thread rod no larger than 7/8". You can run it all the way from the frame through the hood.
- 2-Wire, Chain or bolt the hood down in 6 spots. The all thread through the hood count as (2).
- 3-A 2ft x 2ft hole must be in the hood for fire detection.

Battery

- 1-One battery of any size is permitted in the front passenger floor board.
- 2-Battery must be secured and covered.

Tires

- 1-Any tire size is permitted; NHS tires and skid steer tires are permitted.
- 2-No studded tires; no screws in rims.
- 3-Valve stem protectors are allowed.
- 4-Solid, foam-filled and double tires are permitted.
- 5-No steel plate tire protectors over tires or attached to the rim.

Radiator

- 1-Radiator must remain in the stock position.
- 2-Water tanks and water barrels permitted (Must remain in the stock location.)
- 3-Water tanks and water barrels can be welded or bolted to the core support.
- 4-Water tanks and water barrels can be welded to the frame in two spots on each side of the frame (CANNOT BE WELDED SOLID TO FRAME ON EITHER SIDE.)
- 5-Water tanks and water barrels cannot be mounted to the bumper.

Bumpers

- 1-Any passenger car bumper may be used.
- 2-You may use a homemade bumper. It must be no bigger than 6"x6"x3/8" wall for tube steel and 6 inch SCH 80 pipe 3/8" Wall thickness.
- 3-If you fabricate your own bumper it must be a straight piece of metal; no V or sharp points. Ends must be left open. (Do not cap the ends of the fabricated bumper.)
- 4-Bumpers cannot be wider than the car or fenders. (Measurement will be based off of the narrowest width part of the car.)

5-You may hard nose your frame. You may weld a ¼ inch thick plate no longer than 10 in per frame rail measuring from the back of the bumper and no wider than the frame width. Your preference on top, bottom or side of the frame. You may weld ¼ inch thick x 12 inches long bumper horns to both sides of the frame in place of the 10 inch plate. Bumper horns must not be wider than the frame. Bumper horns may be welded solid.

6- Stock Bumpers may be loaded or stuffed. Must have bumper skin on it.

Rear Differential

- 1-Differentials of any make up to ¾ ton trucks can be used.
- 2-Differentials may be braced from backing plate to backing plate only.
- 3-No excessive bracing on any make or model of differential.

Windshield

1-You must have at least one bar, chain or wire attached to the roof of the car and to the firewall of the car for protection from the hood.

Body Mounts

- 1-Body mount bolts cannot be larger than 5/8. Except for the 7/8 all thread rod going from the frame to the hood through the coil support.
- 2-No extra body mounting bolts.
- 3-Washers cannot be larger than 2 inches made from ¼ inch plate.
- 4-You can run the body mounts through the bottom of the frame.

Body

- 1-No additional / extra metal can be added to the body of the car.
- 2-If you are running a pre run car you can patch sheet metal of same thickness and not to exceed 2 inches past tear in the sheet metal.
- 3-Fender and quarter panels can be bolted. No additional metal may be added. Bolts can only be bolted to the sheet metal of the car. No limit on size or quantity.

Frame

- 1-Frame tilting is allowed. NO ADDITIONAL METAL added to the frame.
- 2-A arms may be welded directly to the frame. No additional metal or steel support on the frame or the A arm.
- 3- Rear hump plates are allowed only on cars running coil springs. Rear hump plates cannot be larger than 4 inches wide by 2 feet long by ¼ inch thick.
- 4-You can weld the hump plate solid. No filling in of factory frame holes.
- 5-If you are running a pre run car and you have a torn or bent frame you can patch that area where it is bent or torn with ¼ inch plate. Patch cannot exceed 1 inch past bend or tear. You can weld the patch plate solid.
- 6-Cannot weld any bar or support from driver's frame rail to passenger frame rail with the exception of the transmission cross member and the rear of the engine cradle support.

7-NO LOADED FRAMES. FRAMES MUST BE EMPTY AND WILL BE CHECKED.

Engine Protectors

1-Engine protectors are allowed.

2-Engine cradles and protectors can be supported from the factory engine cross member for the front engine

support. Engine cradle and protector can be supported from the frame for the rear engine support. The rear engine cradle support can only have one support per side and the support cannot go past the front body mounts.

3-Engine cradles and protectors must tie into the frame by bolting or welding. No adding of additional metal or

support to the frame from the engine cradle or engine protector.

4-Engine cradles or protectors must not tie into the frame or support the frame in any way except for the rear

engine support.

5-Distributor protectors are allowed. May be part of the engine cradle or protector.

Transmission Protectors

1-Transmission protectors are allowed.

2-Transmission protectors can tie into the engine cradle or protector on the front and on the rear of the transmission it must tie into the cross member. TRANSMISSION PROTECTORS CANNOT TIE TO THE FRAME IN ANY

WAY.

Transmission Coolers

1-Transmission coolers are allowed.

2-Transmission coolers must be in the engine compartment if running the cooler on the outside of the car.

3-Transmission coolers can be located inside of the car. If relocated inside of the car it must be kept in the rear

seat area with lines double clamped.

4-If using a separate battery for the fan on the transmission cooler it must not be connected to the battery that

starts the engine or the charging system of the car.

5-Battery must be secured and covered.

Roof Sign

1-Cars must have a 2 ft. by 2 ft. roof sign with the car number on it. Must be bright paint or bright stickers.

2-Roof signs must be securely fastened to the car in such a way as to ensure it does not become detached.

For Questions or Comments... BJ Oliver: 540/765-7853 or Jimmy Williams 540/309-5805